

Empty profile H20 mm

code MFH00.misura/01






PRODUCT DESCRIPTION

Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.

PRODUCT SPECS

Installation method	system
Finishing	White
Dimension	mm



WEB PAGE



ASSEMBLY



OPTIONAL ACCESSORIES

Couple of closure heads H profile

code MFH00C/01

Modular system for direct, diffused and/or accent lighting, consisting of empty profiles made from 90×30 mm painted or anodised extruded aluminium, with a predefined length or cut to measure, to be integrated with LED linear light sources, or projectors. To be completed with side end caps with Light Proof system, opal white diffusing screen or blind closure cover.



Microfile H system - Empty curve profile



code MFH00A1/01

Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



code MFH00A2/01



Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



code MFH00A3/01



Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



code MFH00A4/01



Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



code MFH00B1/01



Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.



code MFH00B2/01

Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



code MFH00B3/01

Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.





code MFH00B4/01

Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



Microfile System - Silicone diffuser



code MFH00TH.misura

Silicone diffuser, to choose, to replace the polycarbonate (already included in the profile), in case you want a different light shield.



Diffuser opal direct/indirect depending on family

Opal diffuser direct for Microfile, indirect for File 30 and Pro Edge, direct/indirect for Microfile H



code MF00P.1000

Square section 6060 aluminium extrusion profile square section measuring 30x30 mm powder-coated colour epoxy powder coated, cut to 1000 mm for ceiling installation, suspension and flush mounting. In the suspension version it is also possible to have indirect light emission.





code MF00P.2000

Square section 6060 aluminium extrusion profile square section measuring 30x30 mm powder-coated colour epoxy powder coated, cut to 2000 mm for ceiling installation, suspension and flush mounting. In the suspension version it is also possible to have indirect light emission.



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

code MF00P.3000

Square section 6060 aluminium extrusion profile square section measuring 30x30 mm powder-coated colour epoxy powder coated, cut to 3000 mm for ceiling installation, suspension and flush mounting. In the suspension version it is also possible to have indirect light emission.



code MF00P.misura

Square section 6060 aluminium extrusion profile square section measuring 30x30 mm powder-coated colour epoxy powder coated, cut to mm for ceiling installation, suspension and flush mounting. In the suspension version it is also possible to have indirect light emission.



Microfile H system – Fixing kit for platerboard



code MFH12

Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.




Technical Sheet

Microfile System Surface mounting kit



code MF00DP.1000

Modular system of 30X30 mm single and bi-emission extruded aluminium profiles, for recessed, ceiling and suspension installation, with LED linear sources and 230/240V electronic ballasts. Its dimensions make it suitable for installation on radiant ceilings by means of appropriate bracket. Painted finish. Diffuser screens in opal polycarbonate and side closing heads with Light Proof system. Degree of protection IP20/ IP40.







Degree of protection IP20/ IP40.



Modular system of 30X30 mm single and bi-emission extruded aluminium profiles, for recessed, ceiling and suspension installation, with LED linear sources and 230/240V electronic ballasts. Its dimensions make it suitable for installation on radiant ceilings by means of appropriate bracket. Painted finish. Diffuser screens in opal polycarbonate and side closing heads with Light Proof system. Degree of protection IP20/ IP40.

Technical Sheet

Microfile H system – Safety kit for ceiling mounting optional

code MFH14

Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



Microfile H system – Power cable kit with ceiling canopy



code MFH01S/01

Modular system of 30X30 mm single and bi-emission extruded aluminium profiles, for recessed, ceiling and suspension installation, with LED linear sources and 230/240V electronic ballasts. Its dimensions make it suitable for installation on radiant ceilings by means of appropriate bracket. Painted finish. Diffuser screens in opal polycarbonate and side closing heads with Light Proof system. Degree of protection IP20/ IP40.



Microfile System Ower cable (L.2000mm) kit with ceiling canopy DRIVER INCLUDED



code MFH00SA/01

system indoor item. Bianco finishing item



code MFH00SB/01

system indoor item. Bianco finishing item



Microfile H System Angle connector



code MFH07/01

Modular system composed of painted extruded aluminum profiles, for suspension and wall installation, available in predefined or customized lengths for direct diffused and double emission lighting. To be integrated with LED linear sources, closing heads with Light Proof system, diffusing screen in opal silicone, suspension cables and canopy. IP44.



Microfile H System – suspension kit linear joint

Microfile H system. Linear joint and suspension kit, including steel cable of L.2000mm.

code MFH08/01

Microfile H system. Linear joint and suspension kit, including steel cable of L.2000mm. Color finish bianco.



Microfile H System Kit Suspension

Suspension kit, steel cable compressor L. 2000 mm.



code MFH09/01

Microfile H, system element. Kit suspension compressive steel cable of L. 2000 mm. 1 kit every 2m profile. Suitable for long profiles. Colour finish bianco.



Microfile H System - SUSPENSION KIT FOR HEAD PROFILE

Microfile H system. Suspension kit with head joint, compressive steel cable of L. 2000 mm.



code MFH10/01

Microfile H system. Suspension kit with head joint, compressive steel cable of L. 2000 mm. Kit to be placed always in the top or tail. Colour finish bianco.

