




Iground Fixed 60

code IG002E.940W/20



PRODUCT DESCRIPTION

Collection of walk-over recessed floor luminaires with integrated Chip On Board LED sources with monochromatic emission, fixed or adjustable optics. The tilting is obtained without having to open the article, thanks to a mechanical movement located on the lamp body. The body, circular in shape, is available in three sizes Ø 65 mm, Ø 84 mm, Ø 132 mm and made of anodized aluminum, with an AISI 316L stainless steel flange, complete with extra-clear tempered safety glass, without visible screws. The fixtures are supplied with 2 meters of neoprene cable. Additional 5m, 10m, 15m or 20m cable is available up upon request. Cylindrical outer casings available. IP67.

PRODUCT SPECS

Installation method	Floor
Light source	LED
Absorbed power	6,7 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Wide 36°
Finishing	Brushed steel
Luminous flux of the product	646 lm
Luminous efficiency	96 lm/W
Life time estimate	3SDCM 50000h L90 B10 Ta 25°C
Energy efficiency class	D
Weight	0.3 Kg
Dimension	L20000xH65 Ø84 mm
Hole size	73 mm
IP Grade	IP67
Protection Class	Class III appliance
Product Spec	Walk-over, Circular shape
Power supply/Transformer	Not included
Protocol	See power supply

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORIES

Box IGround 60



code CCIG02

uncategorized

Technical Sheet

