




# Iground Fixed 100

code IG003B.927S/20









📧 🐼 🔽 🖽 ĽK 🧲

TECHNICAL SHEET 20.05.2024

## **PRODUCT DESCRIPTION**

350

500

D

Collection of walk-over recessed floor luminaires with integrated Chip On Board LED sources with monochromatic emission, fixed or adjustable optics. The tilting is obtained without having to open the article, thanks to a mechanical movement located on the lamp body. The body, circular in shape, is available in three sizes Ø 65 mm, Ø 84 mm, Ø 132 mm and made of anodized aluminum, with an AISI 316L stainless steel flange, complete with extra-clear tempered safety glass, without visible screws. The fixtures are supplied with 2 meters of neoprene cable. Additional 5m, 10m, 15m or 20m cable is available upupon request. Cylindrical outer casings available. IP67.

## PRODUCT SPECS

| Installation method          | Recessed with frame,<br>Floor |
|------------------------------|-------------------------------|
| Light source                 | Led                           |
| Absorbed power               | 12 W / 18 W                   |
| Color temperature            | 2700K                         |
| Color rendering index CRI    | >90                           |
| Optic                        | Spot 14°                      |
| Finishing                    | Acciaio satinato              |
| Luminous flux of the product | 960 lm / 1725 lm              |
| Luminous efficiency          | 80 lm/W / 96 lm/W             |
| MacAdam color tolerance      | 3                             |
| Durata media stimata         | 50000h Ta 25° L70B10          |
| Protocol                     | On/Off                        |
| Energy efficiency class      | D                             |
| Weight                       | 0.8 Kg                        |
| Dimension                    | 5000Hx85 Ø132 mm              |
| Hole size                    | round cut   108 mm            |
| Product Spec                 | Walk-over, Circular shape     |
| gruppi alimentatori          | 500mA                         |

WEB PAGE




#### ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2

### MANDATORY ACCESSORIES

# Accessori Iground Wallbox Iground 100



code CCIG03

uncategorized

**Technical Sheet** 



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.