


## Iground Adjustable 100

code IG005A.930F/20



### PRODUCT DESCRIPTION

Collection of walk-over recessed floor luminaires with integrated Chip On Board LED sources with monochromatic emission, fixed or adjustable optics. The tilting is obtained without having to open the article, thanks to a mechanical movement located on the lamp body. The body, circular in shape, is available in three sizes Ø 65 mm, Ø 84 mm, Ø 132 mm and made of anodized aluminum, with an AISI 316L stainless steel flange, complete with extra-clear tempered safety glass, without visible screws. The fixtures are supplied with 2 meters of neoprene cable. Additional 5m, 10m, 15m or 20m cable is available upupon request. Cylindrical outer casings available. IP67.

### PRODUCT SPECS

Installation method	Recessed with frame, Floor
Light source	Led
Absorbed power	12 W
Color temperature	3000K
Color rendering index CRI	>90
Optic	Flood 24°
Finishing	Acciaio satinato
Luminous flux of the product	1320 lm
Luminous efficiency	110 lm/W
MacAdam color tolerance	3
Durata media stimata	50000h Ta 25° L70B10
Protocol	On/Off
Energy efficiency class	D
Weight	0.8 Kg
Dimension	2000Hx85 Ø132 mm
Hole size	round cut   108 mm
IP Grade	IP67
Product Spec	Adjustable, Walk-over, Circular shape

### WEB PAGE




### ASSEMBLY INSTRUCTIONS



## MANDATORY ACCESSORIES

### Accessori Iground Wallbox Iground 100



code CCIG03

uncategorized

Technical Sheet

