

Iground Adjustable 100

code IG005A.940F/20



PRODUCT DESCRIPTION

Collection of walk-over recessed floor luminaires with integrated Chip On Board LED sources with monochromatic emission, fixed or adjustable optics. The tilting is obtained without having to open the article, thanks to a mechanical movement located on the lamp body. The body, circular in shape, is available in three sizes Ø 65 mm, Ø 84 mm, Ø 132 mm and made of anodized aluminum, with an AISI 316L stainless steel flange, complete with extra-clear tempered safety glass, without visible screws. The fixtures are supplied with 2 meters of neoprene cable. Additional 5m, 10m, 15m or 20m cable is available upupon request. Cylindrical outer casings available. IP67.

PRODUCT SPECS

| | |
|------------------------------|---------------------------------------|
| Installation method | Recessed with frame, Floor |
| Light source | Led |
| Absorbed power | 12 W |
| Color temperature | 4000K |
| Color rendering index CRI | >90 |
| Optic | Flood 24° |
| Finishing | Brushed steel |
| Luminous flux of the product | 1418 lm |
| Luminous efficiency | 118 lm/W |
| MacAdam color tolerance | 3 |
| Durata media stimata | 50000h Ta 25° L70B10 |
| Protocol | On/Off |
| Energy efficiency class | D |
| Weight | 0.8 Kg |
| Dimension | 2000Hx85 Ø132 mm |
| Hole size | round cut 108 mm |
| IP Grade | IP67 |
| Product Spec | Adjustable, Walk-over, Circular shape |

WEB PAGE



ASSEMBLY INSTRUCTIONS



MANDATORY ACCESSORIES

Accessori Iground Wallbox Iground 100



code CCIG03

uncategorized

Technical Sheet

