

## **Iground Adjustable 100**

code IG005C.940W/20



























#### PRODUCT DESCRIPTION

Collection of walk-over recessed floor luminaires with integrated Chip On Board LED sources with monochromatic emission, fixed or adjustable optics. The tilting is obtained without having to open the article, thanks to a mechanical movement located on the lamp body. The body, circular in shape, is available in three sizes Ø 65 mm, Ø 84 mm, Ø 132 mm and made of anodized aluminum, with an AISI 316L stainless steel flange, complete with extra-clear tempered safety glass, without visible screws. The fixtures are supplied with 2 meters of neoprene cable. Additional 5m, 10m, 15m or 20m cable is available upupon request. Cylindrical outer casings available. IP67.

#### **PRODUCT SPECS**

Installation method	Recessed with frame, Floor
Light source	LED
Absorbed power	12 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Wide 40°
Finishing	Brushed steel
Luminous flux of the product	1046 lm
Luminous efficiency	87 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Weight	0.8 Kg
Dimension	L10000xH85 Ø132 mm
Hole size	108 mm
IP Grade	IP67 / IP67
Protection Class	Class III appliance
Product Spec	Adjustable, Walk-over, Circular shape
Power supply/Transformer	Not included
Protocol	See power supply

#### **WEB PAGE**



# **ASSEMBLY**



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

## **MANDATORY ACCESSORIES**

## **Box IGround 100**



code CCIG03 uncategorized

