




Iground Adjustable 100

code IG005E.930W/20







PRODUCT DESCRIPTION

Collection of walk-over recessed floor luminaires with integrated Chip On Board LED sources with monochromatic emission, fixed or adjustable optics. The tilting is obtained without having to open the article, thanks to a mechanical movement located on the lamp body. The body, circular in shape, is available in three sizes Ø 65 mm, Ø 84 mm, Ø 132 mm and made of anodized aluminum, with an AISI 316L stainless steel flange, complete with extra-clear tempered safety glass, without visible screws. The fixtures are supplied with 2 meters of neoprene cable. Additional 5m, 10m, 15m or 20m cable is available upupon request. Cylindrical outer casings available. IP67.

PRODUCT SPECS

| Installation method | Recessed with frame, Floor |
|------------------------------|--|
| Light source | Led |
| Absorbed power | 12 W |
| Color temperature | 3000K |
| Color rendering index CRI | >90 |
| Optic | Wide 40° |
| Finishing | Brushed steel |
| Luminous flux of the product | 974 lm |
| Luminous efficiency | 81 lm/W |
| MacAdam color tolerance | 3 |
| Durata media stimata | 50000h Ta 25° L70B10 |
| Protocol | On/Off |
| Energy efficiency class | D |
| Weight | 0.8 Kg |
| Dimension | 20000Hx85 Ø132 mm |
| Hole size | round cut 108 mm |
| IP Grade | IP67 |
| Product Spec | Adjustable, Walk-over, Circular shape |

WEB PAGE




ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 2

MANDATORY ACCESSORIES

Accessori Iground Wallbox Iground 100



code CCIG03

uncategorized

Technical Sheet



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.