

## File profile recessed with Leva modules

code F1023.930FD/01
















|       | 816  |          |
|-------|------|----------|
| 150_  |      | 150      |
| 02000 |      | 00000    |
|       | 1420 |          |
|       | 1420 |          |
| Û     |      | <u> </u> |



## PRODUCT DESCRIPTION

Direct light indoor recessed lamp made of extruded aluminum 6060, color rendering index CRI >90. Equipped with 2 groups Lever 5 spot series with high color rendering LED sources; 22 W temperature 3000K; fixed optics with aperture 32°; protocol Dimmble Dali / Touch & Dimm. Lamp with finish: white box - black optic. Degree of protection IP20.

## **PRODUCT SPECS**

| Installation method          | Recessed with frame         |
|------------------------------|-----------------------------|
| Light source                 | LED                         |
| Absorbed power               | 10x2,2 W                    |
| Color temperature            | 3000K                       |
| Color rendering index CRI    | >90                         |
| Optic                        | Flood 32°                   |
| Finishing                    | White box - black optic     |
| Luminous flux of the product | 1862 lm                     |
| Luminous efficiency          | 85 lm/W                     |
| MacAdam color tolerance      | 2                           |
| Life time estimate           | 50000h Ta 25° L90B10        |
| Protocol                     | Dimmble Dali / Touch & Dimm |
| Energy efficiency class      | E                           |
| Weight                       | 2.1 Kg                      |
| Dimension                    | L1420 mm                    |
| Hole size                    | 42xL+2 mm                   |
| IP Grade                     | IP20                        |
| Power supply                 | 220-240V 50-60Hz            |

**WEB PAGE** 



**ASSEMBLY** 

