



File suspension with Leva group direct or direct/indirect light

code F1323.940F/01









PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded aluminum 6060, color rendering index CRI >90. Equipped with 2 groups Lever 5 spot series with high color rendering LED sources; temperature 4000K; fixed optics with aperture Flood; protocol On/Off. Lamp with finish: telaio bianco - ottica nera. Degree of protection IP20.

PRODUCT SPECS

Light sourceLedAbsorbed power10x2,2 WColor temperature4000KColor rendering index CRI>90OpticFloodFinishingTelaio bianco - ottica neiLuminaire luminous flux2220 lmLuminous efficiency101 lm/WMacAdam color tolerance2	
Color temperature4000KColor rendering index CRI>90OpticFloodFinishingTelaio bianco - ottica nerLuminaire luminous flux2220 lmLuminous efficiency101 lm/W	
Color rendering index CRI>90OpticFloodFinishingTelaio bianco - ottica nelLuminaire luminous flux2220 lmLuminous efficiency101 lm/W	
OpticFloodFinishingTelaio bianco - ottica nerLuminaire luminous flux2220 lmLuminous efficiency101 lm/W	
FinishingTelaio bianco - ottica nelLuminaire luminous flux2220 lmLuminous efficiency101 lm/W	
Luminaire luminous flux2220 lmLuminous efficiency101 lm/W	
Luminous efficiency 101 lm/W	ra
Maa Adam aalar talaranaa 0	
MacAdam color tolerance 2	
Durata media stimata 50000h Ta 25° L90B10	
Protocol On/Off	
Energy efficiency class E	
Weight 2.40 Kg	
Dimension L1420 mm	
IP Grade IP20	

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time. Page 1 / 1

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it