



File suspension with Leva group direct or direct/indirect light

code F1323.940SD/01









PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded aluminum 6060, color rendering index CRI >90. Equipped with 2 groups Lever 5 spot series with high color rendering LED sources; temperature 4000K; fixed optics with aperture Spot; protocol Dimmable. Lamp with finish: telaio bianco - ottica nera. Degree of protection IP20.

PRODUCT SPECS

Installation method	Suspension
Light source	Led
Absorbed power	10x2,2 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Spot
Finishing	Telaio bianco - ottica nera
Luminaire luminous flux	2220 lm
Luminous efficiency	101 lm/W
MacAdam color tolerance	2
Durata media stimata	50000h Ta 25° L90B10
Protocol	Dimmable
Energy efficiency class	E
Weight	2.40 Kg
Dimension	L1420 mm
IP Grade	IP20

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

LUCIFERO'S SRL with sole shareholder - via del Tappezziere, 3 - 40138 Bologna - Italy - +39 051 6014276 - assistenza@luciferos.it - customercare@luciferos.it