


FORMAT LED 10

code LT3412A



PRODUCT DESCRIPTION

Downlighter outdoor lamp walk-over, complete of led 1,5W beam 16°, color rendering index CRI >80. Grey/brushed steel finishing lamp. ATTENTION: wiring with neoprene cable

PRODUCT FEATURES

Mounting method	downlighter
Lamps	LED
Wattage	1x1,5W
Color temperature	3000K
Color rendering index	>80
Optics	16°
Finishing	grey / brushed steel
Source luminous flux	252lm
Luminous flux	252 lm
Chromaticity tolerance (initial MacAdam)	3
Estimated average life expectancy	50000h L70 B10 ta 25°C
Ballast	not included
Energy efficiency class	A+
Dimension	70x70 H 63 mm
Protection degree	IP67
Installation hole	55
Ip rating	Class III appliance
Adjustable	No
Drive-over	No
Walk-over	Yes
Circular shape	No
Oval shape	No
Soft-rotate & slide mechanism	No
Square shape	No

COMPULSORY ACCESSORIES

LT3410.CC wallbox Format 4-10-12V

ELECTRONICS

1-10V Ballast

AE700.20C.10V.MP

Electronic power supply current 0÷20W 500mA 0÷43V multipower push&dim 1-10V

Dali Ballast

AE700.20CD.MP

Electronic power supply current 0÷20W 500mA 0÷43V multipower dali

AE700.32CD.MP

Electronic power supply current 0÷24W 500mA 0÷47V multipower dali

On/Off Ballast

AE500.6C

Electronic power supply current 0÷6W 500mA 0÷12V

AE500.20C1

Electronic power supply current 0÷20W 500mA 0÷45V

AE700.20C.MP

Electronic power supply current 0÷20W 500mA 0÷40V multipower

AE1050.50C.MP

Electronic power supply current 0÷35W 500mA 0÷72V multipower

