



CI



CI DOWNLIGHT

Apparecchi da incasso a soffitto, fissi od orientabili, con sorgente LED integrata o per lampade GU10 230/240V. Alimentatori, da posizionarsi in remoto, disponibili come accessorio. Corpo, cornice di battuta e gruppo ottico in metallo verniciato o cromato. Installabile anche in soffitti in calcestruzzo o laterizio mediante apposita cassaforma in lamiera zincata disponibile come accessorio. Grado di protezione IP20.

Recessed ceiling luminaires, fixed or adjustable, with integrated LED source or for GU10 230/240V light bulbs. Power supplies, to be positioned remotely, available as accessories. Body, trimmed frame and optical group in painted metal or chromed. It can, also, be installed in concrete or brick ceilings using a special galvanized metal outercasing available as accessory. IP20.





WELCOME TO MINI.

DA OGGI MINI COUNTRYMAN VIAGGA ANCHE SUL TUO CELLULARE.


DA OGGI MINI COUNTRYMAN VIAGGA ANCHE SUL TUO CELLULARE.

CI FISSO - FIXED



CI 35 FISSO PER CARTONGESSO O LATERIZIO CI 35 FIXED FOR PLASTERBOARD OR BRICK WALL

Ø 56 **500**



LED

W	mA	ømm	H	lm prod 3000k 28°	CODE	Col.
5	500	64	80	465	LT1167.9	● ● /01 /02


● Kelvin
27 2700K
30 3000K
40 4000K

● Beam
F 28°

Accessori - accessories: LT9061: cassaforma CI35/35F - wallbox CI35 e CI35/35F

CI 50 FISSO PER CARTONGESSO O LATERIZIO CI 50 FIXED FOR PLASTERBOARD OR BRICK WALL

Ø 70 **350**



W	mA	ømm	H	lm product/beam 3000K		CODE	Col.
				24°	36°		
6,8	350	77	100	330	450	LT1165.9	● ● /01 /02

● Kelvin
27 2700K
30 3000K
40 4000K

● Beam
F 24°
W 36°

W	mA	ømm	H	lm product/beam 3000K		CODE	Col.
				27°	46°		
12	350	77	100	1285	1289	LT1166.9	● ● /01 /02
18	500	77	100	1575	1579		

● Kelvin
27 2700K
30 3000K
40 4000K

● Beam
F 27°
W 46°

CI 50 FISSO PER CARTONGESSO O LATERIZIO CI 50 FIXED FOR PLASTERBOARD OR BRICK WALL



GU10 LED			CODE	Col.
W	ømm	Lmm		
1 x max 50	77	75	LT1165	● ● /01 /02



Accessori - Accessories: LT9062.1: cassaforma CI50/50F - wallbox CI50 e CI50/50F

CI ORIENTABILE - DIRECTIONAL



CI 35 ORIENTABILE PER CARTONGESSO CI 35 DIRECTIONAL FOR PLASTERBOARD

Ø 56 **500**



LED					CODE	Col.
W	mA	Ø	H	lm prod 3000K 28°		
5	500	64	70	465	LT1163.9	/01 /02 /03



● Kelvin
27 2700K
30 3000K
40 4000K

● Beam
F 28°

Solo per cartongesso - Suitable only for plasterboard.

CI 50 ORIENTABILE PER CARTONGESSO CI 50 DIRECTIONAL FOR PLASTERBOARD

Ø 70 **350**



LED					lm product/beam 3000K		CODE	Col.
W	mA	Ø	H	α	24°	36°		
6,8	350	77	100	30	330	450	LT1161.9	/01 /02 /03

● Kelvin
27 2700K
30 3000K
40 4000K

● Beam
F 24°
W 36°


LED					lm product/beam 3000K		CODE	Col.
W	mA	Ø	H	α	27°	46°		
12	350	77	120	30	1285	1289	LT1168.9	/01 /02 /03
18	500	77	120	30	1575	1579		

● Kelvin
27 2700K
30 3000K
40 4000K

● Beam
F 27°
W 46°

Solo per cartongesso - Suitable only for plasterboard.


CI 50 ORIENTABILE GU10 PER CARTONGESSO O LATERIZIO CI 50 DIRECTIONAL GU10 FOR PLASTERBOARD OR BRICK WALL



GU10 LED			CODE	Col.
W	Ømm	Hmm		
1 x max 50	77	90	LT1161	/01 /02 /03

Accessori - Accessories: LT9062.1: cassaforma CI50/50F - wallbox CI50 e CI50/50F


CASSAFORMA WALLBOX



	Dim. LxWmm	Hmm	CODE
CI35	190 x 114	80	LT9061
CI50	208x140	120	LT9062.1

Cassaforma in lamiera zincata per installazione in laterizio o calcestruzzo - galvanized metal wallbox for installing in brick or reinforced concrete

CI35



CI50

