


Microfile soffitto

codice MF011.827/01



MICROFILE LED



DESCRIZIONE PRODOTTO

Series of fixtures to be ceiling-mounted, recessed or trimless-recessed within flat surfaces or to be trimless-recessed in external and internal angles. Direct diffused lighting emission. Linear LED sources, to be completed with remote 24Vdc driver. Available both as default modules and as modules to be assembled in a system. Body in extruded aluminium, painted finish, complete with opal white polycarbonate diffuser. Light Proof system side-end caps. Degree of protection IP40, IP43 or IP67, according to the area where it is installed.

SPECIFICHE PRODOTTO

Metodo di installazione	Soffitto
Sorgente luminosa	Linea-led
Potenza assorbita	19,8 W
Temperatura colore	2700K
Indice di resa cromatica CRI	>80
Finitura	Bianco
Flusso luminoso apparecchio	1610 lm
Efficienza luminosa	81 lm/W
Alimentatore/trasformatore	Non incluso
Protocollo	Vedi alimentatore
Classe di efficienza energetica	D
Peso	0.48 Kg
Dimensione	L925 mm
Grado IP	IP40
Classe di protezione	Apparecchio in classe III

PAGINA WEB



ISTRUZIONI DI MONTAGGIO

