

File 2H sistema - Reglette indiretta LED 24W/m

codice R182IM2.840



DESCRIZIONE PRODOTTO

Modular system for direct, diffused and/or accent lighting, consisting of hollow profiles made from 110x78 mm painted or anodised extruded aluminium, with a predefined length or cut to measure, available in the following versions: wall-mounted, suspended. To be integrated with LED linear light sources, battens for T16 fluorescent lamps, recessed versions with built-in LED source or for QPAR16 halogen/LED lamps and max 16A 3-circuit track modules for inclusion of projectors. Fluorescent battens, complete with 50/60 Hz 230/240 V electronic power supply. LED batten with driver included. To be completed with side end caps with Light Proof system, opal white or microprismatic PC diffusing screen (in accordance with EN 12464-1), closing profiles, with a predefined length or cut to measure, or dark-light aluminium grille with high specular qualities and mounting brackets or suspension cables. IP40 protection rating.

SPECIFICHE PRODOTTO

Metodo di installazione	Sistema
Sorgente luminosa	LED
Potenza assorbita	25,6 W
Temperatura colore	4000K
Indice di resa cromatica CRI	>90
Flusso luminoso apparecchio	4087 lm
Efficienza luminosa	160 lm/W
Tolleranza colore MacAdam	3
Durata media stimata	50000h Ta 25° L70B10
Alimentatore/trasformatore	Incluso
Protocollo	On/Off
Classe di efficienza energetica	E
Dimensione	L1120 mm
Grado IP	IP20
Tensione	220-240V 50-60Hz

PAGINA WEB



ISTRUZIONI DI MONTAGGIO

